

PAUL SCHERRER INSTITUT



PSI Bericht Nr. 12-02

June 2012

ISSN 1019-0643

Nuclear Energy and Safety Research Department
Laboratory for Nuclear Materials

Environmentally-Assisted Cracking in Austenitic Light Water Reactor Structural Materials

Final Report of the KORA-II Project

Hans-Peter Seifert, Stefan Ritter and Hans J. Leber

Paul Scherrer Institut
5232 Villigen PSI
Switzerland
Tel. +41 56 310 21 11
Fax +41 56 310 21 99
www.psi.ch

TABLE OF CONTENTS

ABBREVIATIONS AND SYMBOLS.....	ii
ABSTRACT.....	vi
EXECUTIVE SUMMARY.....	vii
INTRODUCTION.....	xii
PART I:	
Corrosion fatigue crack growth behaviour of austenitic stainless steels under simulated LWR conditions.....	1
PART II:	
Corrosion fatigue initiation and short crack growth behaviour of austenitic stainless steels under simulated LWR conditions.....	31
PART III:	
TMF and isothermal LCF initiation in high-temperature water and air.....	63
PART IV:	
SCC behaviour in the transition region of Alloy 182–low-alloy RPV steel dissimilar metal weld joints in simulated LWR environment.....	81
PART V:	
Detection of SCC by the electrochemical noise technique under simulated BWR conditions: Effect of electrode distance and hydrogen content.....	111
PART VI:	
Effect of chloride on EAC initiation in low-alloy steel.....	125
ANNEX.....	135
ACKNOWLEDGEMENT.....	139