

Technical Report 15-02

**Implementation of the Full-scale
Emplacement Experiment at
Mont Terri:
Design, Construction and
Preliminary Results**

May 2019

Nagra

**National Cooperative
for the Disposal of
Radioactive Waste**

Hardstrasse 73
CH-5430 Wettingen
Switzerland
Tel. +41 56 437 11 11

www.nagra.ch

Table of Contents

Summary	I
Zusammenfassung.....	III
Résumé	VI
Acknowledgements	IX
Table of Contents	XI
List of Tables.....	XV
List of Figures	XVII
1 Introduction	1
1.1 Reference concept.....	1
1.2 Report objectives	3
1.3 Overview of FE Experiment.....	3
1.3.1 Experiment location.....	3
1.3.2 Experiment objectives	5
1.3.3 Experiment Layout	6
1.3.4 Experiment Schedule.....	7
1.3.5 Monitoring system.....	8
1.4 Requirements on the disposal concept.....	10
1.5 Organisation of this Report.....	10
2 Previous THM Experiments in Mont Terri and scoping of the FE Experiment.....	13
2.1 EB Experiment	13
2.2 ESDRED emplacement test.....	15
2.3 HE Experiment Series.....	16
2.3.1 HE-B Experiment	16
2.3.2 HE-D Experiment	18
2.3.3 HE-E Experiment.....	20
2.4 Scoping of the FE Experiment.....	21
3 Construction of the FE Cavern and FE Tunnel and Response of the Rock Mass	29
3.1 Requirements on construction	29
3.2 Monitoring system (Phase 1 and Phase 2a).....	30
3.2.1 Phase 1: Monitoring of Excavation	30
3.2.2 Phase 2a: System for monitoring response to tunnel construction	31
3.3 Rock excavation and support installation.....	32
3.3.1 FE cavern.....	32

3.3.2	FE tunnel.....	33
3.3.2.1	Excavation method	33
3.3.2.2	Support design and installation.....	34
3.3.2.3	Shotcrete mixture.....	35
3.4	Geological mapping and hydro-mechanical behaviour during tunnel construction	37
3.4.1	Geological mapping and tunnel scanning.....	37
3.4.2	Mechanical response to construction and support installation	39
3.5	Summary of tunnel construction.....	42
4	Ventilation period	43
4.1	Requirements on tunnel ventilation period.....	43
4.2	Tunnel climate and near-field rock instrumentation (Phase 2b).....	43
4.3	Ventilation system	44
4.4	Response to ventilation.....	46
4.4.1	Tunnel climate	46
4.4.2	Rock and shotcrete response to ventilation.....	46
4.4.2.1	Monitoring results.....	46
4.5	Summary of ventilation period	47
5	Requirements on, and design of, EBS Materials.....	49
5.1	Requirements on experiment materials and emplacement technology.....	49
5.2	ISS materials.....	52
5.3	Design of the bentonite block pedestal (bentonite blocks)	52
5.3.1	Laboratory testing of production parameters.....	53
5.3.2	BLL.....	55
5.3.3	BeLLT	57
5.3.4	Grono 1	58
5.3.5	Conclusions from design work.....	58
5.4	Design of the heaters	58
5.5	Design of the GBM buffer.....	58
5.6	Design of the concrete plug.....	61
6	Design of emplacement technology, and production and emplacement of EBS materials.....	63
6.1	Requirements on emplacement technology	63
6.2	Preparation for emplacement.....	64
6.3	Production and emplacement of the ISS.....	64
6.4	Production and emplacement of the bentonite block pedestal.....	65
6.4.1	Block production	65
6.4.2	Block storage	66
6.4.3	Emplacement in the FE tunnel.....	67
6.5	Production and emplacement of the heaters	68

6.6	Design, production and emplacement of the GBM buffer.....	68
6.6.1	Design and testing of the backfilling machine.....	68
6.6.1.1	Pre-tests	70
6.6.2	Production and emplacement.....	74
6.7	Design, production and emplacement of the concrete plug.....	76
6.8	Summary of production and emplacement of experiment materials	77
7	Heating phase	79
7.1	Modelling of the heating phase.....	79
7.1.1	Modelling using QPAC	79
7.1.2	Modelling using TOUGH2	86
7.1.3	Requirement on heating power.....	93
7.2	Heating phase monitoring system (Phase 2c and Phase 3).....	94
7.2.1	Instrumentation of the EDZ (Phase 2c)	95
7.2.2	Tunnel wall, bentonite and heater instrumentation (Phase 3).....	95
7.2.2.1	Instrumentation for monitoring of THM processes, gas concentration and metal corrosion.....	95
7.2.2.2	Fibre-optic cables on tunnel wall (Phase 3b).....	98
7.2.2.3	Geophysical methods.....	98
7.2.2.4	Gas monitoring	98
7.2.2.5	Corrosion monitoring.....	99
7.2.3	Data acquisition systems.....	99
7.3	Results of the heating phase	99
7.3.1	Temperature evolution.....	101
7.3.2	Hydraulic evolution: relative humidity in bentonite, tunnel wall and Opalinus Clay	110
7.3.3	Mechanical evolution: deformations	113
7.3.4	Chemical evolution: oxygen consumption and hydrogen generation.....	114
7.4	Summary of the heating phase.....	115
8	Lessons learnt	117
8.1	Design and construction of the FE Experiment	117
8.1.1	Tunnel construction	117
8.1.2	Tunnel ventilation.....	118
8.1.3	Design, production and emplacement of bentonite blocks	118
8.1.4	Design, production and emplacement of GBM	119
8.2	Processes occurring during the heating phases.....	120
8.2.1	Modelling.....	120
8.2.2	Monitoring system.....	121
8.2.3	Experiment evolution.....	121
8.3	Feedback on requirements	125
8.3.1	Evaluation of FE Experiment Performance against Requirements.....	125
8.3.2	Development of requirements.....	128

8.4	Feedback to reference design – TRL assessment	129
9	Conclusions and outlook	137
9.1	Conclusions	137
9.2	Next steps	138
10	References.....	141
Appendix I:	Tunnel lengths and component installation dates	I-1
Appendix II:	Requirements on the FE Experiment.....	II-1
II.1	Requirements on construction	II-1
II.2	Requirements on bentonite.....	II-4
Appendix III:	The FE Experiment data base (FEIS)	III-1
Appendix IV:	Sensor listing.....	IV-1
Appendix V:	List of Materials in the FE Tunnel.....	V-1
Appendix VI:	List of Acronyms	VI-1